




AGAT CLEAN ISO NO FRAME LED CRI95

Recessed luminaires / CRI95 medical device










Luminary is recommended to be used in medical sector to illuminate such premises as: operating rooms, rooms designed for laparoscopic and endoscopic, surgeries and interventions, recovery rooms, dermatological offices and to illuminate blood collection centres, etc. Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. This product is manufactured in production plant which holds quality management system for medical devices ISO 13485.



Maternity ward, Hospital in Goleniów


















Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
AGAT CLEAN ISO NO FRAME LED CRI95 5400	5875	39,2	4000	596 x 596 x 67
AGAT CLEAN ISO NO FRAME LED CRI95 7200	7833	51,8	4000	1196 x 296 x 67 / 596 x 596 x 67
AGAT CLEAN ISO NO FRAME LED CRI95 9000	9791	63,6	4000	596 x 596 x 67
AGAT CLEAN ISO NO FRAME LED CRI95 10800	11750	73,5	4000	1196 x 596 x 67
AGAT CLEAN ISO NO FRAME LED CRI95 14400	15666	102,5	4000	1196 x 596 x 67

Technical drawing:



Light and electrical features:

Light source	LED	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	60000	
Lx/By	L80/B10	
CRI	>95	
SDCM (LED sources)	3	
Operating temperature range [°C]	5 ÷ 30	
Driver	standard on/off (E)	
Power factor cos φ	>0,95	

Mechanical features:

Assembly	mounted in module ceilings
Material	steel sheet
Color	white
Diffuser	SLMR (laminated anti-reflective mat glass)