



#### **BERYL NEW LED COMPACT**

#### Compact









Aluminum cast housing. This technology significantly increases possibility of application of particular luminaire due to lower ceiling load since additional cooling radiator is not required. Beryl New LED O has higher efficiency and efficiency than the previous version. Luminaire is dedicated for prestigious interiors such as hotels, banks and offices of higher standard. Owing to the newest components and renowned producers of LEDs applied it was possible to build such luminaires which save energy consumption comparing with traditional solutions



Cultural Center, Kozienice

















### Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions D x H [mm]
BERYL NEW LED COMPACT O-1 1600	2000 / 2058	12,8	3000 / 4000	Ø100 x 75
BERYL NEW LED COMPACT O-2 2400	3019 / 3108	18,4	3000 / 4000	Ø165 x 100

# **Technical drawing:**





# Light and electrical features:

Light source	LED		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	83000 (1) / 100000 (2) / 100000 (3)/91000 (1) / 100000 (2) / 100000 (3)		
Lx/By	L90/B10 (1) / L80/B10 (2) / L70/B10 (3)		
CRI	>80		
SDCM (LED sources)	3		
Operating temperature range [°C]	5 ÷ 30		
Driver	standard on/off (E)		
Power factor $\cos \phi$	>0,95		

## **Mechanical features:**

Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	aluminum
Color	RAL 9010 (white)
Diffuser	transparent PMMA PLX (PMMA opal) hardened transparent glass