



RUBIN CLEAN NO FRAME LED CRI95

Clean luminaires CRI95









Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body.




















Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
RUBIN CLEAN NO FRAME LED CRI95 3600	3917	27,8	4000	574 x 274 x 69
RUBIN CLEAN NO FRAME LED CRI95 5400	5875	39,2	4000	574 x 574 x 69
RUBIN CLEAN NO FRAME LED CRI95 7200	7833	51,8	4000	1174 x 274 x 69 / 574 x 574 x 69
RUBIN CLEAN NO FRAME LED CRI95 10800	11750	73,5	4000	1174 x 574 x 69
RUBIN CLEAN NO FRAME LED CRI95 14400	15666	102,5	4000	1174 x 574 x 69

Technical drawing:



Light and electrical features:

$\begin{array}{lll} \textbf{Light source} & \textbf{LED} \\ \textbf{Voltage} & 220240 \text{ V}, 5060 \text{ Hz} \\ \textbf{Lifetime of LED sources [h]} & 100000 (1) / 147000 (2) \\ \textbf{Lx/By} & \textbf{L80/B10 (1) / L70/B50 (2)} \\ \textbf{CRI} & >95 \\ \textbf{SDCM (LED sources)} & 3 \\ \textbf{Operating temperature range [°C]} & 5 \div 30 \\ \textbf{Driver} & \text{standard on/off (E)} \\ \textbf{Power factor cos } \phi & >0,95 \\ \end{array}$		
Lifetime of LED sources [h] 100000 (1) / 147000 (2) Lx/By L80/B10 (1) / L70/B50 (2) CRI >95 SDCM (LED sources) 3 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E)	Light source	LED
Lx/By L80/B10 (1) / L70/B50 (2) CRI >95 SDCM (LED sources) 3 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E)	Voltage	220240 V, 5060 Hz
CRI >95 SDCM (LED sources) 3 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E)	Lifetime of LED sources [h]	100000 (1) / 147000 (2)
SDCM (LED sources) 3 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E)	Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E)	CRI	>95
Driver standard on/off (E)	SDCM (LED sources)	3
	Operating temperature range [°C]	5 ÷ 30
Power factor $\cos \varphi$ >0,95	Driver	standard on/off (E)
	Power factor cos φ	>0,95

Mechanical features:

Assembly	surface mounted on ceiling
Material	steel sheet
Color	white
Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass) SHM (hardened mat glass)