



X-LINE SLIM RECESSED LOW UGR LED LINE

Recessed luminaires



Luminaire made of aluminium profile. Compared to traditional X-Line G/K LED, the size has been reduced and the structure enclosed in a narrower profile, which allows a more elegant aspect of the product. X-Line Slim Recessed uses an anti-glare louvre. All this makes it possible to adjust light and create lighting systems, easing the creation of a comfortable view of indoor spaces and their aesthetics. X-Line Slim Recessed is designed for built-in installation on ceilings. The luminaries are adjusted to be linked together with specially designed connectors, which provide great freedom in arranging elements of the system as well as great functionality.


















Main parameters:

		Power of luminaire		
Name	Luminous flux LED [lm]	[W]	Color [K]	Dimensions A x B x H [mm]
X-LINE SLIM RECESSED LOW UGR LED LINE 4200	3940 / 4152	26	3000 / 4000	1142 x 70 x 75 / 1121 x 70 x 75
X-LINE SLIM RECESSED LOW UGR LED LINE 4200 TUNABLE WHITE	3990÷4305 (2700÷6500 K)	25,6	2700 ÷ 6500	1142 x 70 x 75 / 1121 x 70 x 75
X-LINE SLIM RECESSED LOW UGR LED LINE 5250	4925 / 5190	33	3000 / 4000	1422 x 70 x 75 / 1401 x 70 x 75

Technical drawing:





Light and electrical features:

Light source	LED
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)/50000
Lx/By	L80/B10 (1) / L70/B10 (2)/L80/B10
CRI	>80
SDCM (LED sources)	3
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E) DIM DALI (EDD) *
Power factor cos φ	>0,9

^{*} Variant to specify when ordering

Mechanical features:

Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	RASTER (anti-glare louvre)

Additional information:

The luminaire can be made in CLO version.