

Product: ARTSHAPE LINE WALL L-320 UP&DOWN 650/650 PLX EDD 25 830 Index: 19.3001.1004.25



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on the wall. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

Product information		Category Architectural luminaires Family ARTSHAPE LINE WALL Name ARTSHAPE LINE WALL L-3 Index 19.3001.1004.25	$\mathbb{E} \mathbb{P}_{40} \mathbb{K}_{40} \mathbb{E}$
Light and electrical data		Light source	LED
		Luminous flux LED [lm]	1349
		LED power [W]	8
		Luminaire luminous flux [lm]	707
		Power of luminaire [W]	9
		Luminaire's light efficiency [lm/W]	78,6
		Color of the light [K]	3000
		CRI	>80
		SDCM (LED sources)	3
		Beam angle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°
		Photobiological risk class (IEC/EN 62471)	RG0
		Protection against electric shock	I
		Protection degree	IP40
		Voltage	220240 V, 5060 Hz
		Lifetime of LED sources [h]	60000
		Lx/By	L80/B10
		Operating temperature range [°C]	0 ÷ 30
		Driver	DIM DALI (EDD)
		Power factor cos φ	>0,95
		Circuit load capacity	20 (B10), 30 (B16), 32 (C10), 52 (C16)



Mechanical data

ļ	Ă	<u> </u>

Assembly	mounted on wall	
Material	aluminum	
Color	RAL 7016 (anthracite, metallic, fine structure)	
Diffuser	PLX (PMMA opal)	
Impact resistant	IK04	
Dimensions [mm]	320 x 110 x 85	

A graph of light



