

**Product:** ARTSHAPE LINE WALL L-600 UP&DOWN 1300/1300 PLX EDD 25 840

**Index:** 19.3001.2003.25



## Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on the wall. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palette, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

## Product information


Category	<b>Architectural luminaires</b>
Family	<b>ARTSHAPE LINE WALL</b>
Name	<b>ARTSHAPE LINE WALL L-600 UP&amp;DOWN 1300/1300 PLX EDD 25 840</b>
Index	<b>19.3001.2003.25</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>2840</b>
LED power [W]	<b>15</b>
Luminaire luminous flux [lm]	<b>1489</b>
Power of luminaire [W]	<b>17</b>
Luminaire's light efficiency [lm/W]	<b>87,6</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 113,4° / 111,8°</b>
Photobiological risk class (IEC/EN 62471)	<b>RG0</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP40</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>60000</b>
Lx/By	<b>L80/B10</b>
Operating temperature range [°C]	<b>0 ÷ 30</b>
Driver	<b>DIM DALI (EDD)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>17 (B10), 28 (B16), 26 (C10), 41 (C16)</b>

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	600 x 110 x 85

A graph of light

