

## Product: ARTSHAPE LINE WALL L-900 UP&DOWN 1950/1950 PLX E 25 840 Index: 19.3001.3001.25



## Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on the wall. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

Product information		Category Architectural luminaires				
		Family ARTSHAPE LINE WALL Name ARTSHAPE LINE WALL L-900 UP&DOWN 1950/1950 PLX E 25 840				
Light and electrical data		Light sour	се		LED	
		Luminous	flux LED [lm]		4260	
		LED powe	er [W]		23	
		Luminaire	e lumin <mark>ous flux [lm</mark> ]		2234	
		Power of I	luminaire [W]		26	
		Luminaire	s light efficiency [lm/W	]	85,9	
		Color of th	ne light [K]		4000	
		CRI			>80	
		SDCM (LE	ED sources)		3	
		Beam ang	ple [°]		(C0-C180) / (C90-C270) - 113,4° / 111,8°	
		Photobiolo 62471)	ogical risk class (IEC/EN	N	RG0	
		Protection	against electric shock		I	
		Protection	n degree		IP40	
		Voltage			220240 V, 5060 Hz	
		Lifetime o	f LED sources [h]		60000	
		Lx/By			L80/B10	
			temperature range [°C	]	0 ÷ 30	
					standard on/off (E)	
			tor cos φ		>0,95	
		Circuit loa	d capacity		12 (B10), 19 (B16), 20 (C10), 32 (C16)	



## **Mechanical data**

ļ	Ă	<u> </u>

Assembly	mounted on wall		
Material	aluminum		
Color	RAL 7016 (anthracite, metallic, fine structure)		
Diffuser	PLX (PMMA opal)		
Impact resistant	IK04		
Dimensions [mm]	900 x 110 x 85		

## A graph of light



