

## Product: ARTSHAPE LINE WALL L-1150 UP&DOWN 2600/2600 PLX E 25 830 Index: 19.3001.4002.25



## Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on the wall. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

Product information	Category Architectural luminaires   Family ARTSHAPE LINE WALL   Name ARTSHAPE LINE WALL L-1150 UP&DOWN 2600/2600 PLX E 25 830   Index 19.3001.4002.25   Image: Description of the part of
Light and electrical data	Light sourceLEDLuminous flux LED [Im]5396LED power [W]30Luminaire luminous flux [Im]2829Power of luminaire [W]34Luminaire's light efficiency [Im/W]83,2Color of the light [K]3000CRI>80SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 113,4° / 111,8°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockI
	Protection degree   IP40     Voltage   220240 V, 5060 Hz     Lifetime of LED sources [h]   60000     Lx/By   L80/B10     Operating temperature range [°C]   0 ÷ 30     Driver   standard on/off (E)     Power factor cos φ   >0,95     Circuit load capacity   30 (B10), 48 (B16), 43 (C10), 70 (C16)



## Mechanical data

Α	B

Assembly	mounted on wall
Material	aluminum
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	3,1
Dimensions [mm]	1150 x 110 x 85

## A graph of light

