

Product: ARTSHAPE LINE WALL L-1150 UP&DOWN 2600/2600 PLX EDD 34 830

Index: 19.3001.4004.34



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on the wall. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

Product information

Category	Architectural luminaires
Family	ARTSHAPE LINE WALL
Name	ARTSHAPE LINE WALL L-1150 UP&DOWN 2600/2600 PLX EDD 34 830
Index	19.3001.4004.34















Light and electrical data

Light source	LED
Luminous flux LED [lm]	5396
LED power [W]	30
Luminaire luminous flux [lm]	2829
Power of luminaire [W]	34
Luminaire's light efficiency [lm/W]	83,2
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220 240 1/ 50 00 11-
voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	60000
	· · · · · · · · · · · · · · · · · · ·
Lifetime of LED sources [h]	60000
Lifetime of LED sources [h] Lx/By	60000 L80/B10
Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	60000 L80/B10 0 ÷ 30



Mechanical data	Assembly	mounted on wall
	Material	aluminum
$A \longrightarrow A \longrightarrow B \longrightarrow B$	Color	RAL 9016 (white)
1 1	Diffuser	PLX (PMMA opal)
	Impact resistant	IK04
	Dimensions [mm]	1150 x 110 x 85

A graph of light







