

Product: KUBIK WALL ECO LED UP&DOWN 1X G9 IP20 04

Index: 19.3019.1001.04



Description

Luminaire for interchangeable LED sources (called retrofit) with a G9 base. The body is made of aluminum. The open design provides very easy access to the source and its replacement, and very easy mounting on the wall as well. Simple construction giving an interesting light effect. Recommended for decorative lighting of passages, corridors or staircases.

Product information


Category	Architectural luminaires
Family	KUBIK WALL ECO LED IP20
Name	KUBIK WALL ECO LED UP&DOWN 1X G9 IP20 04
Index	19.3019.1001.04



Light and electrical data

Light source	RETROFIT G9 (not included)
Luminous flux LED [lm]	depending on applied light source
LED power [W]	depending on applied light source
Luminaire luminous flux [lm]	depending on applied light source
Power of luminaire [W]	depending on applied light source
Luminaire's light efficiency [lm/W]	depending on applied light source
Color of the light [K]	depending on applied light source
CRI	depending on applied light source
SDCM (LED sources)	depending on applied light source
Beam angle [°]	(C0-C180) / (C90-C270) - 109° / 107,2°
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	depending on applied light source
Lx/By	depending on applied light source
Driver	none

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 9005 (black)
Diffuser	none
Weight [kg]	0,65
Dimensions [mm]	120 x 120 x 120

A graph of light

