

**Product:** MINI WALL C LED UP&DOWN 2X1,7W 3000K E 21

**Index:** 19.3023.2002.21



## Description

Aluminum made luminaire. Thanks to applied lenses of renowned producers there is possibility to arrange luminous flux UP/DOWN. MINI WALL C LED UP&DOWN is recommended to be installed as a decorative and accent lighting.

## Product information


Category	Architectural luminaires
Family	MINI WALL C LED
Name	MINI WALL C LED UP&DOWN 2X1,7W 3000K E 21
Index	19.3023.2002.21



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	248
LED power [W]	3
Luminaire luminous flux [lm]	206
Power of luminaire [W]	5
Luminaire's light efficiency [lm/W]	41,2
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	5
Beam angle [°]	(C0-C180) / (C90-C270) - 9,6° / 37°
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	50000
Lx/By	L70/B50
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,5
Circuit load capacity	80 (B10), 157 (B16), 265 (C10), 317 (C16)

## Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 9006 (gray, metallic, fine structure)
Diffuser	transparent polycarbonate
Impact resistant	IK04
Weight [kg]	0,66
Dimensions [mm]	200 x 90 x 45

A graph of light

