

Product: AGAT LED 13200 PLX E 840 / 1200X600

Index: 19.3038.0509.34



Description

Luminary dedicated for module and suspended ceilings with the T24 grid, equipped with the highly efficient LED sources. Luminary body made from steel sheet, powder coated in white. Monolithic construction is the characteristic feature of the luminaire (remaining in one-piece during exploitation process). Luminary available in PLX or Micro-PRM diffuser. Luminary dedicated for the public use structure.

Product information

Category	Recessed luminaires
Family	AGAT LED
Name	AGAT LED 13200 PLX E 840 / 1200X600
Index	19.3038.0509.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	13695
LED power [W]	70,2
Luminaire luminous flux [lm]	10138
Power of luminaire [W]	71,6
Luminaire's light efficiency [lm/W]	141,6
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 102,8° / 102,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20/44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	8 (B10), 12 (B16), 13(C10), 21 (C16)

Mechanical data



Assembly	mounted in module ceilings
Material	steel sheet
Color	white
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	7,35
Dimensions [mm]	1196 x 596 x 90

A graph of light

