

**Product:** EUROPANEL LED 3800 MICRO-PRM EDD 34 IP65 840

**Index:** 19.3054.0115.34



## Description

Modern LED panel for installation in suspended ceilings or directly on the ceiling. Equipped with the highly efficient LED sources. Luminaire body made from aluminum. PMMA opal diffuser. Colour of luminary - white. Luminary dedicated for the public use structure like offices, conference rooms, classrooms, lecture halls etc. The level of protection against solid substances, dust and moisture penetration is IP65.

## Product information

Category	<b>Recessed luminaires</b>
Family	<b>EUROPANEL LED IP65</b>
Name	<b>EUROPANEL LED 3800 MICRO-PRM EDD 34 IP65 840</b>
Index	<b>19.3054.0115.34</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>3479</b>
LED power [W]	<b>18</b>
Luminaire luminous flux [lm]	<b>2634</b>
Power of luminaire [W]	<b>21</b>
Luminaire's light efficiency [lm/W]	<b>125,4</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 93° / 82,6°</b>
Photobiological risk class (IEC/EN 62471)	<b>RG0</b>
Protection against electric shock	<b>II</b>
Protection degree	<b>IP65</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>63000 (1) / 53000 (2)</b>
Lx/By	<b>L70/B50 (1) / L80/B10 (2)</b>
Operating temperature range [°C]	<b>5 ÷ 30</b>
Driver	<b>DIM DALI (EDD)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>33 (B10), 55 (B16), 42 (C10), 67 (C16)</b>

## Mechanical data



Assembly	mounted in module ceilings, plasterboard ceilings or directly on the ceiling
Material	aluminum
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	596 x 596 x 36

## A graph of light

