

**Product:** X-LINE G/K LED 3900 MICRO-PRM E 24 830 LINE-S / CONNECTOR TYPE-TB 600/600/600

**Index:** 19.3061.0002.24



## Description

The group of X-line luminaires is made of aluminum profile with opal diffuser or micro-prismatic diffuser. The luminaires may be joined with special connectors providing great freedom in arranging elements of the system and its functionality.

## Product information


Category	Recessed luminaires
Family	X-LINE G/K LED CONNECTOR T
Name	X-LINE G/K LED 3900 MICRO-PRM E 24 830 LINE-S / CONNECTOR TYPE-TB 600/600/600
Index	19.3061.0002.24



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	3788
LED power [W]	20
Luminaire luminous flux [lm]	2853
Power of luminaire [W]	21,7
Luminaire's light efficiency [lm/W]	131,5
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°
Protection against electric shock	I
Protection degree	IP20/44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	30 (B10), 48 (B16), 43 (C10), 70 (C16)

## Mechanical data



Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	anodised aluminum
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	1126 x 603 x 134
Mounting hole [mm]	1126 x 598 x 70

## A graph of light

