

Product: X-LINE G/K LED 3900 MICRO-PRM EDD 24 830 LINE-1S / CONNECTOR TYPE-TA 600/600/600

Index: 19.3061.0007.24



Description

The group of X-line luminaires is made of aluminum profile with opal diffuser or micro-prismatic diffuser. The luminaires may be joined with special connectors providing great freedom in arranging elements of the system and its functionality.

Product information

Category **Recessed luminaires**

Family **X-LINE G/K LED CONNECTOR T**

Name **X-LINE G/K LED 3900 MICRO-PRM EDD 24 830 LINE-1S / CONNECTOR TYPE-TA 600/600/600**


Index **19.3061.0007.24**



Light and electrical data

Light source	LED
Luminous flux LED [lm]	3788
LED power [W]	20
Luminaire luminous flux [lm]	2853
Power of luminaire [W]	21,7
Luminaire's light efficiency [lm/W]	131,5
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°
Protection against electric shock	I
Protection degree	IP20/44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)

Mechanical data



Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	anodised aluminum
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	1126 x 603 x 134
Mounting hole [mm]	1126 x 598 x 70

A graph of light

