

Product: AMETYST NEW LED 4000 PC E IP65 840 MWS

Index: 19.3071.0015.34



Description

Surface mounted or wall luminaire equipped in highly efficient LED panels. Luminaire body and diffuser made from IK10 impact resistant material. Luminaire recommended for: bathrooms, wards, medical staff room and also in outdoor areas. The product is equipped with a microwave motion sensor.

Product information


Category	Surface mounted luminaires
Family	AMETYST NEW LED
Name	AMETYST NEW LED 4000 PC E IP65 840 MWS
Index	19.3071.0015.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4103
LED power [W]	23
Luminaire luminous flux [lm]	3230
Power of luminaire [W]	25,8
Luminaire's light efficiency [lm/W]	125,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 112,6° / 112,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	68000
Lx/By	L80/B10
Operating temperature range [°C]	-20 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	39 (B10), 62 (B16), 65 (C10), 104 (C16)

Mechanical data



Assembly	surface mounted on ceiling or on wall
Material	polycarbonate
Color	white
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK10
Weight [kg]	1,23
Dimensions [mm]	Ø356 x 76

A graph of light

