

Product: ESSENCE LED 2600 PLX E 33 830 / L-1134MM

Index: 19.3081.0001.33



Description

Luminaire made from aluminum profile adapted to be mounted on suspensions, or directly on a solid ceiling construction. Its body made from anodized aluminum profil. There are two colors available: white (RAL9016) or grey (RAL9006). Its diffuser is made from white polymethyl methacrylate. Luminaire to be used in offices, conference halls, all structures of public sectors.

Product information


Category	Surface mounted luminaires
Family	ESSENCE LED
Name	ESSENCE LED 2600 PLX E 33 830 / L-1134MM
Index	19.3081.0001.33



Light and electrical data

Light source	LED
Luminous flux LED [lm]	2525
LED power [W]	13,3
Luminaire luminous flux [lm]	1755
Power of luminaire [W]	14,4
Luminaire's light efficiency [lm/W]	121,9
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 96° / 74,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)

Mechanical data



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	aluminum
Color	RAL 9010 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1,4
Dimensions [mm]	1134 x 36 x 63

A graph of light

