

Product: MATRIX SURFACE LED 8800 MICRO-PRM 21 E 830

Index: 19.3087.0007.21



Description

Decorative luminary of direct light distribution. Is characterized by high lighting parameters and subtle construction. Casing of the luminary is made of powder-painted steel sheet. Grey is a standard colour of the luminary. Significant diversity of the value of luminous flux. Colour rendering index CRI: 80. The luminary perfectly matches interior design of representative facilities.

Product information


Category	Surface mounted luminaires
Family	MATRIX SURFACE LED
Name	MATRIX SURFACE LED 8800 MICRO-PRM 21 E 830
Index	19.3087.0007.21



Light and electrical data

Light source	LED
Luminous flux LED [lm]	8811
LED power [W]	46,8
Luminaire luminous flux [lm]	6542
Power of luminaire [W]	49,1
Luminaire's light efficiency [lm/W]	133,2
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	15 (B10), 25 (B16), 24 (C10), 38 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9006 (gray, metallic, fine structure)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	5
Dimensions [mm]	1245 x 160 x 62

A graph of light

