

Product: PLAFOND ROUND LED 1300 PC E IP54 840 EDRE12/WH/4000

Index: 19.3092.0001.34



Description

Surface mounted or wall luminaire equipped in highly efficient LED panels. Luminaire body and diffuser made from IK10 impact resistant material.

Product information

| | |
|----------|-----------------------------------------------------|
| Category | Surface mounted luminaires |
| Family | PLAFOND ROUND LED |
| Name | PLAFOND ROUND LED 1300 PC E IP54 840 EDRE12/WH/4000 |
| Index | 19.3092.0001.34 |





Light and electrical data


| | |
|-------------------------------------|------------------------------------------|
| Light source | LED |
| Luminous flux LED [lm] | 1600 |
| LED power [W] | 12 |
| Luminaire luminous flux [lm] | 1065 |
| Power of luminaire [W] | 14 |
| Luminaire's light efficiency [lm/W] | 76,1 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 117,8° / 117,8° |
| Protection against electric shock | II |
| Protection degree | IP54 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 54000 |
| Lx/By | L90 |
| Operating temperature range [°C] | 0 ÷ 40 |
| Driver | standard on/off (E) |

Mechanical data

| | |
|------------------|---------------------------------------|
| Assembly | surface mounted on ceiling or on wall |
| Material | polycarbonate |
| Color | white |
| Diffuser | PC (opalescent polycarbonate) |
| Impact resistant | IK10 |
| Dimensions [mm] | Ø280 x 63 |



A graph of light



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%.
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 23-12-2022