

Product: PLAFOND ROUND LED 2000 PC E IP54 840 EDRE18/WH/4000**Index:** 19.3092.0003.34

Description

Surface mounted or wall luminaire equipped in highly efficient LED panels. Luminaire body and diffuser made from IK10 impact resistant material.

Product information


Category	Surface mounted luminaires
Family	PLAFOND ROUND LED
Name	PLAFOND ROUND LED 2000 PC E IP54 840 EDRE18/WH/4000
Index	19.3092.0003.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	2480
LED power [W]	20
Luminaire luminous flux [lm]	1651
Power of luminaire [W]	23
Luminaire's light efficiency [lm/W]	71,8
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 117,8° / 117,8°
Protection against electric shock	II
Protection degree	IP54
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	54000
Lx/By	L90
Operating temperature range [°C]	0 ÷ 40
Driver	standard on/off (E)

Mechanical data



Assembly	surface mounted on ceiling or on wall
Material	polycarbonate
Color	white
Diffuser	PC (opallescent polycarbonate)
Impact resistant	IK10
Dimensions [mm]	Ø280 x 63

A graph of light

