

Product: AGALINE LED 12000 E 34 840 / L-1685MM

Index: 19.3120.0010.34



Description

Agaline is an industrial modular system for installing in straight lines. Agaline is an excellent option for lighting industrial premises and warehouses, but is also suitable for offices, supermarkets and commercial spaces. A luminaire mounted in line systems, made of sheet steel, painted in white. Individual elements of the system combined with connectors. Through-cabling ensures easy and fast installation. To be applied in industrial objects and other places, where high intensity and uniformity of lighting is necessary.

Product information

Category	Industrial luminaires
Family	AGALINE LED
Name	AGALINE LED 12000 E 34 840 / L-1685MM
Index	19.3120.0010.34















Light and electrical data

Light source	LED
Luminous flux LED [lm]	12495
LED power [W]	77
Luminaire luminous flux [lm]	12220
Power of luminaire [W]	86
Luminaire's light efficiency [lm/W]	142,1
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 114,4° / 114,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Duete etiene de enere	
Protection degree	IP20
Voltage	IP20 220240 V, 5060 Hz
Voltage	220240 V, 5060 Hz
Voltage Lifetime of LED sources [h]	220240 V, 5060 Hz 100000 (1) / 147000 (2)
Voltage Lifetime of LED sources [h] Lx/By	220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2)
Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2) 5 ÷ 35



Mechanical data		Assembly	surface mounted on slings
A	□iH B	Material	steel sheet
		Color	RAL 9016 (white)
		Diffuser	none
		Impact resistant	IK04
		Dimensions [mm]	1685 x 56 x 45

A graph of light







