

**Product:** UNIVERSAL LINE LED 16000 PLX E 24 IP65 840 KRW3K / L-2288MM

**Index:** 19.3127.0051.24



## Description

Universal Line system is built on the base of aluminium profile of crosswise dimension after assembly 60 mm x 75 mm, LED strips and linear lenses. Standard colour - natural anodized aluminium. Installation: - surface mounted line (spring plates to the ceiling) - suspended line. The construction of the luminaire ensures one of the three levels of protection: IP20, IP55 or IP65. IP20 and IP65 versions of the product are dedicated for internal use. Versions IP55 of the luminaire are dedicated for external use. In order to achieve the level of protection IP55, luminaires should be installed purely and simply on a horizontal surface, illuminating part should be directed downwards. It is forbidden to install the luminaire on the wall or directed upwards.

## Product information


Category	Industrial luminaires
Family	UNIVERSAL LINE LED
Name	UNIVERSAL LINE LED 16000 PLX E 24 IP65 840 KRW3K / L-2288MM
Index	19.3127.0051.24



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	16660
LED power [W]	95
Luminaire luminous flux [lm]	12532
Power of luminaire [W]	106
Luminaire's light efficiency [lm/W]	118,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	12 (B10), 20 (B16), 21 (C10), 34 (C16)

## Mechanical data



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	4,6
Dimensions [mm]	2288 x 60 x 75

A graph of light

