

**Product:** RUBIN SPORT NEW LED 8000 MICRO-PRM KR E 34 830 / 1190X220MM

**Index:** 19.3135.0001.34



## Description

Surface mounted luminary dedicated for the sports, gymnastics and squash halls, etc. Luminary equipped with the protecting grid made from steel wire powder coated. Diffuser used in the luminary provides less glare effect for the room users when compared to the light sources used in the fluorescents.

## Product information

Category	Industrial luminaires
Family	RUBIN SPORT NEW LED
Name	RUBIN SPORT NEW LED 8000 MICRO-PRM KR E 34 830 / 1190X220MM
Index	19.3135.0001.34



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	8052
LED power [W]	51
Luminaire luminous flux [lm]	6047
Power of luminaire [W]	57
Luminaire's light efficiency [lm/W]	106,1
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 90,2° / 99,6°
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	16 (B10), 26 (B16), 23 (C10), 37 (C16)

## Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK10
Weight [kg]	7,95
Dimensions [mm]	1190 x 220 x 60

## A graph of light

