

Product: RUBIN SPORT NEW LED 32000 MICRO-PRM KR EDD 34 840 /1190X320

Index: 19.3135.0028.34



Description

Surface mounted luminary dedicated for the sports, gymnastics and squash halls, etc. Luminary equipped with the protecting grid made from steel wire powder coated. Diffuser used in the luminary provides less glare effect for the room users when compared to the light sources used in the fluorescents.

Product information

Category Industrial luminaires

Family RUBIN SPORT NEW LED

Name RUBIN SPORT NEW LED 32000 MICRO-PRM KR EDD 34 840 /1190X320

Index 19.3135.0028.34
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	33320
LED power [W]	204
Luminaire luminous flux [lm]	25023
Power of luminaire [W]	228
Luminaire's light efficiency [lm/W]	109,8
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 90,2° / 99,6°
Protection against electric shock	I
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	9 (B10), 16 (B16), 9 (C10), 16 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK10
Weight [kg]	10,33
Dimensions [mm]	1190 x 320 x 60



A graph of light

