

**Product:** UPDOOR MINI LED 2000 PC 840 E IP65 25

**Index:** 19.3137.0001.25



## Description

Powder painted steel housing. Possibility of mounting emergency module. Isolated battery applied in luminaire is equipped with thermostat enabling performance in low temperature up to -25° C. Updoor Mini might be mounted on walls or ceilings and is recommended to illuminate buildings' entrances, arteries, tunnels, underground entrances, etc.

## Product information



Category	Outdoor luminaires
Family	UPDOOR MINI LED
Name	UPDOOR MINI LED 2000 PC 840 E IP65 25
Index	19.3137.0001.25



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	2055
LED power [W]	12
Luminaire luminous flux [lm]	1295
Power of luminaire [W]	14
Luminaire's light efficiency [lm/W]	92,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	2
Beam angle [°]	(C0-C180) / (C90-C270) - 100,6° / 103,2°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	>100000
Lx/By	L80/B10
Operating temperature range [°C]	5÷30 / -25÷30 THERMOSTAT
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	61 (B10), 98 (B16), 102 (C10), 164 (C16)

## Mechanical data



Assembly	mounted on wall
Material	steel sheet
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK08
Weight [kg]	1,5
Dimensions [mm]	190 x 150 x 150

## A graph of light

