

Product: KUBIK WALL ECO LED UP OR DOWN 2X GU10 IP54 25 Index: 19.3165.0006.25



Description

Voltage

Lx/By

Driver

Beam angle [°]

Protection degree

Protection against electric shock

Lifetime of LED sources [h]

Luminaire for removable LED sources, called Retofit, matching the GU10 holder. The body is made of aluminum painted with a special facade paint resistant to weather conditions. PMMA opal. Very easy assembly and access to the interior. Recommended for balconies lighting.

Product	inform	ation

Category **Outdoor luminaires** Family **KUBIK WALL ECO LED IP54** KUBIK WALL ECO LED UP OR DOWN 2X GU10 IP54 25 Name Index 19.3165.0006.25 $\mathbf{E} \square \mathbf{P}_{54}$

Light and	electrical	data
-----------	------------	------

Light source	RETROFIT GU10 (not included)
Luminous flux LED [lm]	depending on applied light source
LED power [W]	depending on applied light source
Luminaire luminous flux [lm]	depending on applied light source
Power of luminaire [W]	depending on applied light source
Luminaire's light efficiency [lm/W]	depending on applied light source
Color of the light [K]	depending on applied light source
CRI	depending on applied light source
SDCM (LED sources)	depending on applied light source

220..240 V, 50..60 Hz

(C0-C180) / (C90-C270) - 111,4° / 111,4°

depending on applied light source

depending on applied light source

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	PMMA opal
Weight [kg]	1,2
Dimensions [mm]	200 x 120 x 100

L

IP54

none

A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 23-12-2022