

Product: KUBIK WALL LONG LED UP OR DOWN 1100 840 E IP65 04

Index: 19.3166.0002.04



Description

A luminaire made for illuminating building facades. The body is made of aluminum painted with special facade paint which is resistant to bad weather conditions. Energy-efficient fitting made of component parts produced by renowned companies. Ergonomic shapes of the fitting enable the application almost in every building. The assembly is very easy. The fitting is featured by a high level of protection against the penetration of solids and water IP65.

Product information


Category	Outdoor luminaires
Family	KUBIK WALL LONG LED UP OR DOWN
Name	KUBIK WALL LONG LED UP OR DOWN 1100 840 E IP65 04
Index	19.3166.0002.04



Light and electrical data

Light source	LED
Luminous flux LED [lm]	1161
LED power [W]	6
Luminaire luminous flux [lm]	550
Power of luminaire [W]	7
Luminaire's light efficiency [lm/W]	78,6
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 108,6° / 109,4°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 9005 (black)
Diffuser	PMMA opal
Impact resistant	IK08
Weight [kg]	1,35
Dimensions [mm]	324 x 125 x 100

A graph of light

