

**Product:** STREETPARK M LED PREMIUM HO 15000 STREET-S E IP66 22 757

**Index:** 19.3174.0008.22



## Description

Powder painted aluminum cast housing highly weather proof. Luminaire is equipped with adjustable handle designed for mounting on posts and arms of 60 mm diameter. Level of tightness IP66. Diffuser is made of hardened glass. Following color temperatures are available: 5700 K. It is possible to program an autonomous multi-level or manual power reduction for specific customer needs by using a specialized power supply in the luminaire. The luminaires have overvoltage protection as standard based on the functionality of the power supplies. Optionally, the luminaires can be equipped with an additional voltage surge protector that does not require interference during the assembly and disassembly of the power supply system. \*Selected luminary variants are available with ENEC certificate.

## Product information

Category	<b>Outdoor luminaires</b>
Family	<b>STREETPARK M LED PREMIUM</b>
Name	<b>STREETPARK M LED PREMIUM HO 15000 STREET-S E IP66 22 757</b>
Index	<b>19.3174.0008.22</b>




## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>14900</b>
LED power [W]	<b>97</b>
Luminaire luminous flux [lm]	<b>11381</b>
Power of luminaire [W]	<b>107</b>
Luminaire's light efficiency [lm/W]	<b>106,4</b>
Color of the light [K]	<b>5700</b>
CRI	<b>&gt;70</b>
SDCM (LED sources)	<b>5</b>
Beam angle [°]	<b>street light distribution</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP66</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>60000</b>
Lx/By	<b>L70/B10</b>
Operating temperature range [°C]	<b>-40 ÷ 40</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>6 (B10), 10 (B16), 10 (C10), 17 (C16)</b>

## Mechanical data

Assembly	<b>mounted on poles</b>
Material	<b>aluminum</b>
Color	<b>RAL 9007 (dark gray)</b>
Diffuser	<b>hardened transparent glass</b>
Impact resistant	<b>IK09</b>
Dimensions [mm]	<b>718 x 311 x 103</b>



## A graph of light

