

Product: AGAT CLEAN NO FRAME LED 6600 SHM E IP65 840 / 600X600

Index: 19.3186.0028.34



Description

Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. Luminary recommended for: operating and treatment rooms, as well as intensive care units. *Selected luminary variants are available with ENEC certificate.

Product information

Category Clean luminaires - recessed
Family AGAT CLEAN NO FRAME LED
Name AGAT CLEAN NO FRAME LED 6600 SHM E IP65 840 / 600X600
Index 19.3186.0028.34


















Light and electrical data

Light source	LED
Luminous flux LED [lm]	6848
LED power [W]	33,7
Luminaire luminous flux [lm]	5512
Power of luminaire [W]	35,3
Luminaire's light efficiency [lm/W]	156,1
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	16 (B10), 25 (B16), 26(C10), 42 (C16)

Mechanical data



Assembly	mounted in module ceilings
Material	steel sheet
Color	white
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Weight [kg]	6,7
Dimensions [mm]	596 x 596 x 67
Mounting hole [mm]	580 x 580



A graph of light

