

**Product:** NEPTUN LED COMPACT V2 1300 PC-FROZEN E 21 IP66 840 / L-600 ZASILANIE PRZELOTOWE 16A

**Index:** 19.3207.0022.21



## Description

Tightly-closed ceiling luminaires with highly efficient LED light sources, ensuring additional protection against solid body penetration and jet of water from all directions. Perfect to be installed in moist and dusty rooms. The luminaire is characterized by compact size and unbelievably simple and quick way to install comparing with similar products. The color temperature for applied LED light sources is 3000/4000 K. Color rendering index Ra>80. The luminaire is dedicated for halls, warehouses, underground passes, car parks illumination etc. Looping through power supply 16 A.

## Product information

Category	<b>Compact</b>
Family	<b>NEPTUN LED COMPACT V2</b>
Name	<b>NEPTUN LED COMPACT V2 1300 PC-FROZEN E 21 IP66 840 / L-600 ZASILANIE PRZELOTOWE 16A</b>
Index	<b>19.3207.0022.21</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>1880</b>
LED power [W]	<b>10</b>
Luminaire luminous flux [lm]	<b>1722</b>
Power of luminaire [W]	<b>10,7</b>
Luminaire's light efficiency [lm/W]	<b>160,9</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 123,6° / 116°</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP66</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>70000</b>
Lx/By	<b>L80/B10</b>
Operating temperature range [°C]	<b>-25 ÷ 40</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>46 (B10), 74 (B16), 72 (C10), 115 (C16)</b>

## Mechanical data



Assembly	<b>directly mounted to ceiling construction or surface mounted on slings</b>
Material	<b>polycarbonate</b>
Color	<b>RAL 9006 (grey)</b>
Diffuser	<b>PC-FROZEN (frozen polycarbonate)</b>
Impact resistant	<b>IK10</b>
Dimensions [mm]	<b>620 x 72 x 60</b>

## A graph of light

