

Product: X-LINE SLIM RECESSED LED 5500 MICRO-PRM EDD 34 840 / L-1441MM

Index: 19.3218.0009.34



Description

Luminaire made of aluminium profile. Compared to traditional X-Line G/K LED, the size has been reduced and the structure enclosed in a narrower profile, which allows a more elegant aspect of the product. X-Line Slim Recessed uses an opaline Micro PRM diffuser. All this makes it possible to adjust light and create lighting systems, easing the creation of a comfortable view of indoor spaces and their aesthetics. X-Line Slim Recessed is designed for built-in installation on ceilings.

Product information

Category	Recessed luminaires
Family	X-LINE SLIM RECESSED LED
Name	X-LINE SLIM RECESSED LED 5500 MICRO-PRM EDD 34 840 / L-1441MM
Index	19.3218.0009.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	5727
LED power [W]	29
Luminaire luminous flux [lm]	4256
Power of luminaire [W]	30,5
Luminaire's light efficiency [lm/W]	139,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
Protection against electric shock	I
Protection degree	IP40
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B10 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,9
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)

Mechanical data

Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	1441 x 70 x 75
Mounting hole [mm]	1431 x 55



A graph of light

