

**Product:** AGAT CLEAN CLASS 5-6 NO FRAME LED 13200 SLM E IP65 830 KRG3K / 1200X600**Index:** 19.3225.0079.34

## Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 5-6. Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body.

## Product information

|          |   |
|----------|---|
| Category | Clean Class 3-9   |
| Family   | AGAT CLEAN CLASS 5-6 NO FRAME LED                                       |
| Name     | AGAT CLEAN CLASS 5-6 NO FRAME LED 13200 SLM E IP65 830 KRG3K / 1200X600 |
| Index    | 19.3225.0079.34   |



## Light and electrical data

|                                     |  |
|-------------------------------------|--|
| Light source                        | LED                                    |
| Luminous flux LED [lm]              | 13217                                  |
| LED power [W]                       | 70,2                                   |
| Luminaire luminous flux [lm]        | 10589                                  |
| Power of luminaire [W]              | 71,6                                   |
| Luminaire's light efficiency [lm/W] | 147,9                                  |
| Color of the light [K]              | 3000                                   |
| CRI                                 | >80                                    |
| SDCM (LED sources)                  | 3                                      |
| Beam angle [°]                      | (C0-C180) / (C90-C270) - 100° / 100,2° |
| Protection against electric shock   | I                                      |
| Protection degree                   | IP65                                   |
| Voltage                             | 220..240 V, 50..60 Hz                  |
| Lifetime of LED sources [h]         | 100000 (1) / 147000 (2)                |
| Lx/By                               | L80/B10 (1) / L70/B50 (2)              |
| Operating temperature range [°C]    | 5 ÷ 30                                 |
| Driver                              | standard on/off (E)                    |
| Power factor cos φ                  | >0,95                                  |
| Circuit load capacity               | 8 (B10), 12 (B16), 13(C10), 21 (C16)   |

## Mechanical data



|                  |                            |
|------------------|----------------------------|
| Assembly         | mounted in module ceilings |
| Material         | steel sheet                |
| Color            | white                      |
| Diffuser         | SLM (laminated mat glass)  |
| Impact resistant | IK08                       |
| Dimensions [mm]  | 1196 x 596 x 67            |

## A graph of light

