

**Product:** STREETPARK S LED COMPACT HO 10000 SHM E IP66 22 757

**Index:** 19.3250.0003.22



## Description

Powder painted aluminum cast housing highly weather proof. Luminaire is equipped with adjustable handle designed for mounting on posts and arms of 60 mm diameter. Level of tightness IP66. Diffuser is made of hardened glass. Following color temperatures are available: 5700 K.

## Product information


Category	<b>Compact</b>
Family	<b>STREETPARK LED COMPACT</b>
Name	<b>STREETPARK S LED COMPACT HO 10000 SHM E IP66 22 757</b>
Index	<b>19.3250.0003.22</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>11175</b>
LED power [W]	<b>76</b>
Luminaire luminous flux [lm]	<b>8808</b>
Power of luminaire [W]	<b>83</b>
Luminaire's light efficiency [lm/W]	<b>106,1</b>
Color of the light [K]	<b>5700</b>
CRI	<b>&gt;70</b>
SDCM (LED sources)	<b>5</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 98,8° / 102°</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP66</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>60000</b>
Lx/By	<b>L70/B10</b>
Operating temperature range [°C]	<b>-40 ÷ 40</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>6 (B10), 10 (B16), 10 (C10), 17 (C16)</b>

## Mechanical data



Assembly	<b>mounted on poles</b>
Material	<b>aluminum</b>
Color	<b>RAL 9007 (dark gray)</b>
Diffuser	<b>SHM (hardened mat glass)</b>
Impact resistant	<b>IK09</b>
Dimensions [mm]	<b>628 x 266 x 99</b>

## A graph of light

