

**Product:** X-LINE LED COMPACT 2000 PLX E 24 840 / L-572MM

**Index:** 19.3252.0002.24



## Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver. X-LINE fittings are intended to be mounted on ceiling or pendants. In the family of X-LINE LED fittings modules of renowned brands are applied.

## Product information

Category	Compact
Family	X-LINE LED COMPACT
Name	X-LINE LED COMPACT 2000 PLX E 24 840 / L-572MM
Index	19.3252.0002.24



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	2302
LED power [W]	12
Luminaire luminous flux [lm]	1535
Power of luminaire [W]	14
Luminaire's light efficiency [lm/W]	109,6
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109° / 107,2°
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	50000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)

## Mechanical data



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1,5
Dimensions [mm]	572 x 63 x 74

## A graph of light

