

Product: ARTSHAPE LINE LED LARGE SUSPENDED TW 4000 PLX EDD 34 827-865 / S-1,5M Index: 19.4009.3453.34



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. LED modules adjusted to regulate the color temperature of light in the range from 2700 K to 6500 K.

Product information	Category Architectural luminaires Family ARTSHAPE LINE LED		
	Index 19.4009.3453.34		
	$\overbrace{LED} (\overbrace{ED}) (\overbrace{ED}) (\overbrace{LED}) (\overbrace{ED})) (\overbrace{ED}) (\overbrace$	Ø	
	Light and electrical data	Light source LED	
Luminous flux LED [Im] 4080			
LED power [W] 36			
Luminaire luminous flux [lm] 2140			
Power of luminaire [W] 39			
Luminaire's light efficiency [lm/W] 54,9			
Color of the light [K] 2700 ÷ 6500			
CRI >80			
SDCM (LED sources) 4			
Beam angle [°] (C0-C180) / (C90-C270) - 113,4° / 12		11,8°	
Protection against electric shock			
Protection degree IP40			
Voltage 220240 V, 5060 Hz			
Lifetime of LED sources [h] 60000			
Lx/By L80/B10			
Operating temperature range [°C] 0 ÷ 30			
Driver DIM DALI (EDD)			
Power factor $\cos \varphi$ >0,95			
Circuit load capacity 13 (B10), 21 (B16), 22 (C10), 36 (C1		L 6)	
Mechanical data	Assembly surface mounted on slings		
	T Material aluminum		
	Color RAL 9016 (white)		
	Diffuser PLX (PMMA opal)		
	Impact resistant IK04		
	Dimensions [mm] 1640 x 80 x 80		

A graph of light



