

## Product: ARTSHAPE OVAL LED LARGE UP&DOWN 4000/12000 PLX E 34 840 / S-1,5M Index: 19.4010.6723.34




## Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

Product information		Category Architectural luminaires		
		Family ARTSHAPE OVAL LED		
		Name ARTSHAPE OVAL LED LARGE UP&DOWN 4000/12000 PLX E 34 840 / S-1,5M		
		Index 19.4010.6723.34		
Light and electrical data		Light source	LED	
		Luminous flux LED [lm]	3952 / 11880	
		LED power [W]	30/86	
		Luminaire luminous flux [lm]	12244	
		Power of luminaire [W]	128	
		Luminaire's light efficiency [lm/W]	95,7	
		Color of the light [K]	4000	
		CRI	>80	
		SDCM (LED sources)	4	
		Beam angle [°]	(C0-C180) / (C90-C270) - 111,2° / 114,2°	
		Protection against electric shock	I	
		Protection degree	IP40	
		Voltage	220240 V, 5060 Hz	
		Lifetime of LED sources [h]	35000	
		Lx/By	L80/B10	
		Operating temperature range [°C]	0 ÷ 30	
		Driver	standard on/off (E)	
		Power factor $\cos \phi$	>0,95	
		Circuit load capacity	5 (B10), 7 (B16), 8 (C10), 12 (C16)	
Mechanical data		Assembly	surface mounted on slings	
	T I	Material	aluminum	
	1500	Color	RAL 9016 (white)	
	4	Diffuser	PLX (PMMA opal)	
		Impact resistant	IK04	
	<u>·                                      </u>	Dimensions [mm]	1170 x 250 x 85	

## A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 23-12-2022