


## Product: ARTSHAPE ROUND LED MEDIUM EDGE SUSPENDED 4500 PLX E 34 840 / S-1,5M Index: 19.4012.2221.34



## Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

111,8°

RG0

**IP40** 

60000

0 ÷ 30

>0,95

L80/B10

220..240 V, 50..60 Hz

standard on/off (E)

15 (B10), 25 (B16), 24 (C10), 38 (C16)

I

Product information	Catego	bry Architectural luminaires
	Family	ARTSHAPE ROUND LED
	Name	ARTSHAPE ROUND LED MEDIUM EDGE SUSPENDED 4500 PLX E 34 840 / S-1,5M
	Index	19.4012.2221.34
		$\underbrace{}_{\text{LED}} \underbrace{}_{\text{LED}} \underbrace{}_{\text{ED}} \underbrace{}_{\text{HO}} \underbrace{HO} \underbrace{}_{\text{HO}} \underbrace{}_{\text{HO}} \underbrace{}_{\text{HO}} \underbrace{}_{H$
Light and electrical data	Light so	ource LED
	Lumino	ous flux LED [lm] 4455
	LED po	ower [W] 32
	Luminai	aire luminous flux [lm] 2336
	Power of	of luminaire [W] 35
	Lumina	aire's light efficiency [lm/W] 66,7
	Color of	of the light [K] 4000
	CRI	>80
	SDCM (	(LED sources) 3
	Beam a	angle [°] (C0-C180) / (C90-C270) - 113,4° /

Photobiological risk class (IEC/EN

Protection against electric shock

Operating temperature range [°C]

Lifetime of LED sources [h]

62471)

Voltage


Lx/By

Driver

Protection degree

Power factor cos φ Circuit load capacity

## Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	Ø900 x 85

## A graph of light

