

Product: ARTSHAPE ROUND LED MEDIUM EDGE SUSPENDED 9000 PLX EDD 34 840 / S-1,5M Index: 19.4012.2423.34




Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

Product information	Category Architectural luminaires		
	Family ARTSHAPE ROUND LED		
	Name ARTSHAPE ROUND LED MEDIUM EDGE SUSPENDED 9000 PLX EDD 34 840 / S-1,5M		
	Index 19.4012.2423.34		
	$\overbrace{LED} \textcircled{\mathbb{E}} \mathbb{E} \textcircled{\mathbb{E}} \mathbb{E} \textcircled{\mathbb{E}} \mathbb{E} \textcircled{\mathbb{E}} \mathbb{E} \textcircled{\mathbb{E}} \mathbb{E} \mathbb{E} \mathbb{E} \mathbb{E} \mathbb{E} \mathbb{E} E$	A	
Light and electrical data	Light source LED		
	Luminous flux LED [lm] 8910		
	LED power [W] 64		
	Luminaire luminous flux [lm] 4672		
	Power of luminaire [W] 70		
	Luminaire's light efficiency [lm/W] 66,7		
	Color of the light [K] 4000		
	CRI >80		
	SDCM (LED sources) 3		
	Beam angle [°] (C0-C180) / (C90-C270) - 113,4 111,8°	°	
	Photobiological risk class (IEC/EN RG0 62471)		
	Protection against electric shock		
	Protection degree IP40		
	Voltage 220240 V, 5060 Hz		
	Lifetime of LED sources [h] 60000		
	Lx/By L80/B10		
	Operating temperature range [°C] 0 ÷ 30		
	Driver DIM DALI (EDD)		
	Power factor cos φ >0,95		
	Circuit load capacity 14 (B10), 23 (B16), 22 (C10), 3	5 (C16)	

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	Ø900 x 85

A graph of light

