


Product: ARTSHAPE ROUND LED LARGE EDGE SUSPENDED 12000 PLX E 34 830 / S-1,5M

Index: 19.4012.3611.34



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

Product information

Category Architectural luminaires		
Family	ARTSHAPE ROUND LED	
Name	ARTSHAPE ROUND LED LARGE EDGE SUSPENDED 12000 PLX E 34 830 / S-1,5M	
Index	19.4012.3611.34	

















Light source	LED
Luminous flux LED [lm]	12512
LED power [W]	94,4
Luminaire luminous flux [lm]	6561
Power of luminaire [W]	108
Luminaire's light efficiency [lm/W]	60,8
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	0 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95

Mechanical data





Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	7,5
Dimensions [mm]	Ø1200 x 85



A graph of light

