

Product: ARTSHAPE ROUND LED SMALL FULL SUSPENDED 4000 PLX E 34 830 / S-1,5M Index: 19.4013.1711.34



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

220..240 V, 50..60 Hz

standard on/off (E)

15 (B10), 24 (B16), 24 (C10), 40 (C16)

60000 L80/B10

0 ÷ 30

>0,95

Product information		Category	Architectural luminaires	5
		Family	•	
		Name		
		Index	19.4013.1711.34	
			CE	
Light and electrical data		Light sou	urce	LED
		Luminou	is flux LED [lm]	4280
		LED pov	ver [W]	32
		Luminair	e luminous flux [lm]	3148
		Power of	f luminaire [W]	35
		Luminair	e's light efficiency [lm/W]	89,9
		Color of	the light [K]	3000
		CRI		>80
		SDCM (I	_ED sources)	3
		Beam ar	ngle [°]	(C0-C180) / (C90-C270) - 111,2° / 114,2°
		Photobic 62471)	ological risk class (IEC/EN	RG0
		Protectio	on against electric shock	I
		Protectio	on degree	IP20

Voltage

Lx/By


Driver

Lifetime of LED sources [h]

Power factor cos φ Circuit load capacity

Operating temperature range [°C]

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	Ø650 x 85

A graph of light

