

Product: ARTSHAPE SIX LED LARGE EDGE SUSPENDED 6000 PLX EDD 34 840 / S-1,5M Index: 19.4015.3323.34




Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

Product information	Category Architectural luminaires	Category Architectural luminaires	
	Family ARTSHAPE SIX LED	Family ARTSHAPE SIX LED Name ARTSHAPE SIX LED LARGE EDGE SUSPENDED 6000 PLX EDD 34 840 / S-1,5M	
	Index 19.4015.3323.34		
Light and electrical data	Light source LED		
	Luminous flux LED [lm] 5940		
	LED power [W] 46		
	Luminaire luminous flux [lm] 3115		
	Power of luminaire [W] 50		
	Luminaire's light efficiency [lm/W] 62,3		
	Color of the light [K] 4000		
	CRI >80		
	SDCM (LED sources) 3		
	Beam angle [°] (C0-C1 111,8°	.80) / (C90-C270) - 113,4° /	
	Photobiological risk class (IEC/EN RG0 62471)		
	Protection against electric shock		
	Protection degree IP40		
	Voltage 2202 4	40 V, 5060 Hz	
	Lifetime of LED sources [h] 60000		
	Lx/By L80/B 1	LO	
	Operating temperature range [°C] 0 ÷ 30		
	Driver DIM D/	ALI (EDD)	
	Power factor cos φ >0,95		
	Circuit load capacity 14 (B1	0), 23 (B16), 22 (C10), 35 (C16)	

Mechanical data



Assembly	surface mounted on slings	
Material	aluminum	
Color	RAL 9016 (white)	
Diffuser	PLX (PMMA opal)	
Impact resistant	IK04	
Dimensions [mm]	1170 x 1043 x 85	

A graph of light

