

Product: ARTSHAPE SQ LED MEDIUM EDGE SUSPENDED 6000 PLX E 34 840 / S-1,5M

Index: 19.4017.2321.34



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

Product information

Category	Architectural luminaires
Family	ARTSHAPE SQ LED
Name	ARTSHAPE SQ LED MEDIUM EDGE SUSPENDED 6000 PLX E 34 840 / S-1,5M
Index	19 4017 2321 34
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	5940
LED power [W]	46
Luminaire luminous flux [lm]	3115
Power of luminaire [W]	50
Luminaire's light efficiency [lm/W]	62,3
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Voltage Lifetime of LED sources [h]	
	220240 V, 5060 Hz
Lifetime of LED sources [h]	220240 V, 5060 Hz 60000
Lifetime of LED sources [h] Lx/By	220240 V, 5060 Hz 60000 L80/B10
Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	220240 V, 5060 Hz 60000 L80/B10 0 ÷ 30



Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	7,13
Dimensions [mm]	930 x 930 x 85

A graph of light



