

Product: X-LINE SLIM LOW UGR L-DOWN LED 4200 RASTER DAISY-BLACK-WIDE EDD 34 840 / L-1126MM S-1,5M

Index: 19.4088.1223.34



Description

The luminaire is made of aluminum profile. Light distribution in the lower half-space. Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses an anti-glare louver. It allows to create lighting systems, facilitating the creation of comfortable vision in the interiors. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information

Category	Surface mounted luminaires
Family	X-LINE SLIM LOW UGR L-DOWN LED
Name	X-LINE SLIM LOW UGR L-DOWN LED 4200 RASTER DAISY-BLACK-WIDE EDD 34 840 / L-1126MM S-1,5M
Index	19.4088.1223.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4475,1
LED power [W]	22,5
Luminaire luminous flux [lm]	3713
Power of luminaire [W]	25,2
Luminaire's light efficiency [lm/W]	147,3
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 72,6° / 74,4°
Protection against electric shock	I
Protection degree	IP40
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B10 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	RASTER (anti-glare louver)
Impact resistant	IK04
Weight [kg]	2,3
Dimensions [mm]	1126 x 48 x 70

A graph of light

