

Product: X-LINE SLIM LOW UGR L-DOWN LED 8400 RASTER DAISY-BLACK-WIDE E 34 840 / L-2248MM S-1,5M

Index: 19.4088.2421.34



Description

The luminaire is made of aluminum profile. Light distribution in the lower half-space. Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses an anti-glare louver. It allows to create lighting systems, facilitating the creation of comfortable vision in the interiors. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information

| | |
|----------|--|
| Category | Surface mounted luminaires |
| Family | X-LINE SLIM LOW UGR L-DOWN LED |
| Name | X-LINE SLIM LOW UGR L-DOWN LED 8400 RASTER DAISY-BLACK-WIDE E 34 840 / L-2248MM S-1,5M |
| Index | 19.4088.2421.34 |



Light and electrical data

| | |
|-------------------------------------|--|
| Light source | LED |
| Luminous flux LED [lm] | 8950 |
| LED power [W] | 45 |
| Luminaire luminous flux [lm] | 7427 |
| Power of luminaire [W] | 50,4 |
| Luminaire's light efficiency [lm/W] | 147,4 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 72,6° / 74,4° |
| Protection against electric shock | I |
| Protection degree | IP40 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 100000 (1) / 147000 (2) |
| Lx/By | L80/B10 (1) / L70/B10 (2) |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 16 (B10), 26 (B16), 23 (C10), 37 (C16) |

Mechanical data



| | |
|------------------|----------------------------|
| Assembly | surface mounted on slings |
| Material | aluminum |
| Color | RAL 9016 (white) |
| Diffuser | RASTER (anti-glare louver) |
| Impact resistant | IK04 |
| Dimensions [mm] | 2248 x 48 x 70 |

A graph of light

