



#### **TOPAZ ODG CLEAN AL LED CRI95**

#### Clean luminaires CRI95









Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Body of the luminaire made of steel sheet powder coated in white. Special construction of the luminaire allows opening it from the top. Thanks to this, maintenance can be done without littering facilities. Product is equipped in highly efficient LED light source.




















## Main parameters:

| Name                              | Luminous flux LED [lm] | Power of luminaire [W] | Color [K]   | Dimensions A x B x H [mm] |
|-----------------------------------|------------------------|------------------------|-------------|---------------------------|
| TOPAZ ODG CLEAN AL LED CRI95 5400 | 5964,5 / 6213          | 40,7                   | 3000 / 4000 | 657 x 626 x 50-105        |
| TOPAZ ODG CLEAN AL LED CRI95 7200 | 7952,6 / 8284          | 54,2                   | 3000 / 4000 | 657 x 626 x 50-105        |
| TOPAZ ODG CLEAN AL LED CRI95 9000 | 9940,8 / 10355         | 67,8                   | 3000 / 4000 | 657 x 626 x 50-105        |

# **Technical drawing:**



# Light and electrical features:

| Light source                              | LED                                     |
|---|---|
| Voltage                                   | 220240 V, 5060 Hz                       |
| Lifetime of LED sources [h]               | 100000                                  |
| Lx/By                                     | L80/B10                                 |
| CRI                                       | >95                                     |
| SDCM (LED sources)                        | 3                                       |
| Photobiological risk class (IEC/EN 62471) | RG0                                     |
| Operating temperature range [°C]          | 5 ÷ 30                                  |
| Driver                                    | standard on/off (E)<br>DIM DALI (EDD) * |
| Power factor cos φ                        | >0,95                                   |

<sup>\*</sup> Variant to specify when ordering

## **Mechanical features:**

| Assembly | for specialty or concrete ceilings  |
|----------|---|
| Material | steel sheet   |
| Color    | RAL 9010 (white)  |
| Diffuser | Micro-PRM (micro-prismatic diffuser PMMA) Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass) PLX (PMMA opal) SHM (hardened mat glass) |