




UPDOOR MINI LED

Outdoor luminaires









Powder painted steel housing. Possibility of mounting emergency module. Isolated battery applied in luminaire is equipped with thermostat enabling performance in low temperature up to -25° C. Updoor Mini might be mounted on walls or ceilings and is recommended to illuminate buildings' entrances, arteries, tunnels, underground entrances, etc.



Local marketplace, Brwinów















Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
UPDOOR MINI LED 2000	2055	14	4000	190 x 150 x 150

Technical drawing:





Light and electrical features:

Light source	LED	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	>100000	
Lx/By	L80/B10	
CRI	>80	
SDCM (LED sources)	2	
Operating temperature range [°C] -20÷30 / -25÷30 THERMOST		
Driver	standard on/off (E)	
Power factor cos φ	>0,95	

^{*} Variant to specify when ordering

Mechanical features:

Assembly	mounted on wall
Material	steel sheet
Color	RAL 9005 (black) RAL 7016 (anthracite, metallic, fine structure) RAL 9016 (white) *
Diffuser	PC (opalescent polycarbonate)