





X-LINE SLIGHT UP&DOWN LED

Surface mounted luminaires





Linear luminaire with minimized width. Made of aluminum profile 34 mm wide and 68 mm high. Mounted on slings. Direct-indirect light distribution. The optical system is fulfilled by an aperture recessed into the body, facing the end cap. Available opal smooth or microprismatic diffuser made of PMMA. Diffuser used for indirect distribution (on top of the luminaire) available only in PLX-T version (transparent PMMA). Luminaire in single version. Available colours: anodized aluminum, black (RAL 9005), grey (RAL 9006), white (RAL 9016) or any RAL colour on request. End cap aluminum, painted in the colour of the body. Use of luminaires typically for offices, public spaces, community areas in multi-family buildings.



Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
X-LINE SLIGHT UP&DOWN LED 1100/2200	3340,1 / 3594,2	19,4	3000 / 4000	572 x 34 x 68
X-LINE SLIGHT UP&DOWN LED 1950/2600	4908,9 / 5284	27,3	3000 / 4000	1134 x 34 x 68
X-LINE SLIGHT UP&DOWN LED 3250/3900	7713,7 / 8303,9	42,8	3000 / 4000	1693 x 34 x 68
X-LINE SLIGHT UP&DOWN LED 3300/4400	7792,2 / 8387,5	45,3	3000 / 4000	1134 x 34 x 68
X-LINE SLIGHT UP&DOWN LED 4550/5200	10518,5 / 11323,6	58,4	3000 / 4000	2256 x 34 x 68
X-LINE SLIGHT UP&DOWN LED 5500/6600	12244,1 / 13180,8	71,3	3000 / 4000	1693 x 34 x 68
X-LINE SLIGHT UP&DOWN LED 650/1300	2104,2 / 2264,3	12,1	3000 / 4000	572 x 34 x 68
X-LINE SLIGHT UP&DOWN LED 7700/8800	16696,1 / 17974,1	97,2	3000 / 4000	2256 x 34 x 68

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	80000/145000
Lx/By	L80/B10/L90/B10
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E) DIM DALI (EDD) *
Power factor cos φ	>0,95

* Variant to specify when ordering

Mechanical features:

Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9005 (black) RAL 9006 (grey) anodised aluminum RAL 9016 (white) *
Diffuser	PLX-T/Micro-PRM (transparent PMMA/micro-prismatic diffuser PMMA) [up/down] PLX-T/PLX (transparent PMMA/PMMA opal) [up/down]

Note: The power shown refers to the whole system (tolerance +/- 10%).
The given luminous flux refers to LED light sources (tolerance +/- 10% depends on the value of the colour temperature).
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 30-06-2025