




# X-LINE SLIM RECESSED LOW UGR LED LINE

#### **Recessed luminaires**









Luminaire made of aluminium profile. Compared to traditional X-Line G/K LED, the size has been reduced and the structure enclosed in a narrower profile, which allows a more elegant aspect of the product. X-Line Slim Recessed uses an anti-glare louvre. All this makes it possible to adjust light and create lighting systems, easing the creation of a comfortable view of indoor spaces and their aesthetics. X-Line Slim Recessed is designed for built-in installation on ceilings. The luminaries are adjusted to be linked together with specially designed connectors, which provide great freedom in arranging elements of the system as well as great functionality.


















#### Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
X-LINE SLIM RECESSED LOW UGR LED 4200 LINE	4212 / 4432	25,5	3000 / 4000	1133 x 70 x 75 / 1121 x 70 x 75
X-LINE SLIM RECESSED LOW UGR LED LINE 4200 TUNABLE WHITE	3990÷4305 (2700÷6500 K)	25,6	2700 ÷ 6500	1133 x 70 x 75 / 1121 x 70 x 75
X-LINE SLIM RECESSED LOW UGR LED 5250 LINE	5265 / 5540	31,8	3000 / 4000	1413 x 70 x 75 / 1401 x 70 x 75

# **Technical drawing:**





# **Light and electrical features:**

Light source	LED		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	100000/50000		
Lx/By	L80/B10		
CRI	>80		
SDCM (LED sources)	3		
Photobiological risk class (IEC/EN 62471)	RG0		
Operating temperature range [°C]	5 ÷ 35		
Driver	standard on/off (E) DIM DALI (EDD) *		
Power factor cos φ	>0,95		

<sup>\*</sup> Variant to specify when ordering

### **Mechanical features:**

Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	RAL 9005 (black) RAL 9006 (grey) anodised aluminum RAL 9016 (white) *
Diffuser	RASTER (anti-glare louver)

#### Additional information:

The luminaire can be made in CLO version.