



AGAT CLEAN SLIGHT LED

Clean luminaires - recessed



Luminary designed to module suspended ceilings. Light distribution made by using high performance lenses. Luminary body made from steel sheet, powder coated in white. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.




Cosmetics laboratory Dr Irena Eris, Piaseczno



Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
AGAT CLEAN SLIGHT LED 2600	2538 / 2672	13,9	3000 / 4000	595 x 595 x 35
AGAT CLEAN SLIGHT LED 3900	3807,2 / 4007,5	20,8	3000 / 4000	595 x 595 x 35
AGAT CLEAN SLIGHT LED 4400	4442 / 4675	24,4	3000 / 4000	595 x 595 x 35
AGAT CLEAN SLIGHT LED 5200	5076,2 / 5343,4	27,8	3000 / 4000	595 x 595 x 35
AGAT CLEAN SLIGHT LED 6600	6662,5 / 7013,2	36,6	3000 / 4000	595 x 595 x 35
AGAT CLEAN SLIGHT LED 8800	8883,4 / 9350,9	48,8	3000 / 4000	595 x 595 x 35

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E) DIM DALI (EDD) *
Power factor cos φ	>0,95

* Variant to specify when ordering

Mechanical features:

Assembly	mounted in module ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SH (transparent hardened glass)

Note: The power shown refers to the whole system (tolerance +/- 10%).
The given luminous flux refers to LED light sources (tolerance +/- 10% depends on the value of the colour temperature).
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 22-08-2025

Dodatkowe informacje / Additional information / Zusätzliche Informationen:

Wszystkie produkty CLEAN przeznaczone do montażu w sufitach podwieszanych są standardowo wyposażone w zaczep do podwieszenia opraw do części sufitu stałego (odciążenie konstrukcji sufitu).

All CLEAN products dedicated for installation in suspended ceilings are equipped with a hook as a standard solution for suspending the luminaires to a part of the fixed ceiling (relieving the suspended ceiling structure).

Alle CLEAN-Produkte geeignet für den Einbau in abgehängten Decken sind standardmäßig mit einem Haken zum Aufhängen der Leuchten an einem Teil der festen Decke ausgestattet (Belastung der Deckenkonstruktion wird verringert).

