



## AGAT LED DECO SMOOTH

### Recessed luminaires



Housing luminaire for suspended module ceilings. Housing made of steel sheet powder coated in white. Characteristic feature of Agat LED Deco Smooth is 'inserted' diffuser, which after the luminaire is mounted is above the level of ceiling. This solution gives very interesting, original and decorative effect. The luminaire is available with milky colour diffuser PLX or micro-prismatic and is equipped with highly efficient LED light source. The colour temperature 3000 K or 4000 K. The luminaire is recommended to illuminate public utility facilities.




Luxiona Poland office, Warsaw



Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
AGAT LED DECO SMOOTH 5400	5222 / 5383,1	27,8	3000 / 4000	595 x 595 x 120
AGAT LED DECO SMOOTH 7500	7337,2 / 7564,1	39,9	3000 / 4000	595 x 595 x 120

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	80000
Lx/By	L80/B10
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E) DIM DALI (EDD) *
Power factor cos φ	>0,95

\* Variant to specify when ordering

Mechanical features:

Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA) PLX (PMMA opal)

Additional information:

The luminaire can be made in CLO version.

Note: The power shown refers to the whole system (tolerance +/- 10%).  
The given luminous flux refers to LED light sources (tolerance +/- 10% depends on the value of the colour temperature).  
Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 25-07-2025